



| NOZZLE | DESCRIPTION | SIZE | QTY | FILTER PERFORMANCE | |
|--------|----------------|-----------|-----|---------------------------------|------|
| N1 | INLET | 8" 150# | 1 | MAX FLOW RATE (gpm) | 1600 |
| N2 | OUTLET | 8" 150# | 1 | SCREEN AREA (ft. ²) | 5.00 |
| N3 | FLUSH OUTLET | 2" FNPT | 1 | MAX TEMP. (°F) | 150 |
| N4 | SERVICE PORT | 3.5" 150# | 1 | MAX PRES. (psi) | 150 |
| N5 | COUPLING | 1" FNPT | 2 | VESSEL WEIGHT (lbs) | 150 |
| K1 | HYD CONNECTION | ¼" FNPT | 2 | | |
| K2 | HYD CONNECTION | ¼" FNPT | 2 | | |
| K3 | HYD CONNECTION | ¼" FNPT | 2 | | |

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 TOLERANCES
 DECIMALS ANGULAR
 .XX + .05 ± 0.5 DEG.
 .XXX ± .01

FORSTA FILTERS
Self-Cleaning Water Filters

B8-FRP180

| | | | |
|-------|----------|-----------|--------|
| SIZE | FSCM NO. | DWG NO. | REV |
| | | B8-FRP180 | 0 |
| SCALE | SHEET | | 1 of 1 |
| 3.50 | | | |